US00RE44161E

(19) **United States**

(12) **Reissued Patent**

Matlin et al.

(10) **Patent Number: US RE44,161 E**

(45) **Date of Reissued Patent: Apr. 23, 2013**

(54) **SHREDDER WITH THICKNESS DETECTOR**

(75) Inventors: **Tai Hoon K. Matlin**, Round Lake Beach, IL (US); **Eric Gach**, Mount Prospect, IL (US)

(73) Assignee: **Fellowes, Inc.**, Itasca, IL (US)

(21) Appl. No.: **13/030,849**

(22) Filed: **Feb. 18, 2011**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **7,631,822**
Issued: **Dec. 15, 2009**
Appl. No.: **11/444,491**
Filed: **Jun. 1, 2006**

U.S. Applications:

(63) Continuation-in-part of application No. 11/177,480, filed on Jul. 11, 2005, now Pat. No. 7,661,614, and a continuation-in-part of application No. 11/385,864, filed on Mar. 22, 2006, now Pat. No. 7,798,435.

(51) **Int. Cl.**

B02C 4/32	(2006.01)
B02C 7/14	(2006.01)
B02C 9/04	(2006.01)
B02C 11/08	(2006.01)

(52) **U.S. Cl.**
USPC **241/36**; 241/100; 241/236

(58) **Field of Classification Search** 241/36, 241/37.5, 100, 236
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,221,516 A		4/1937	Hathaway	
3,619,537 A	*	11/1971	Hosokawa et al.	219/723
3,724,166 A	*	4/1973	van der Meer	53/334
3,724,766 A		4/1973	Bosland	
3,764,819 A	*	10/1973	Muller	307/116
3,785,230 A		1/1974	Lokey	

(Continued)

FOREIGN PATENT DOCUMENTS

DE	3313232	10/1984
DE	8619856.4	10/1988

(Continued)

OTHER PUBLICATIONS

English Translation of Japanese Patent Application Publication No. 9-38513, published on Feb. 10, 1997.

(Continued)

Primary Examiner — Bena Miller

(74) *Attorney, Agent, or Firm* — Pillsbury Winthrop Shaw Pittman LLP

(57) **ABSTRACT**

A shredder is disclosed. The shredder includes a housing having a throat for receiving at least one article to be shredded, and a shredder mechanism received in the housing and including an electrically powered motor and cutter elements. The shredder mechanism enables the at least one article to be shredded to be fed into the cutter elements. The motor is operable to drive the cutter elements so that the cutter elements shred the articles fed therein. The shredder also includes a detector that is configured to detect a thickness of the at least one article being received by the throat, and a controller that is operable to perform a predetermined operation responsive to the detector detecting that the thickness of the at least one article is at least equal to a predetermined maximum thickness.

7 Claims, 9 Drawing Sheets



U.S. PATENT DOCUMENTS

3,829,850	A		8/1974	Guetersloh
3,929,850	A	*	12/1975	Streck et al. 556/431
3,947,734	A	*	3/1976	Fyler 361/181
4,192,467	A		3/1980	Hatanaka
4,352,980	A		10/1982	Hibari
4,378,717	A		4/1983	Schneider et al.
4,489,897	A		12/1984	Turner
4,495,456	A		1/1985	Vercillo et al.
4,497,478	A		2/1985	Reschenhofer
4,683,381	A		7/1987	Dufoug
4,683,391	A		7/1987	Dufoug
4,707,704	A		11/1987	Allen
4,757,949	A		7/1988	Horton
4,814,632	A		3/1989	Glaeser
4,815,669	A		3/1989	Fujii
4,842,205	A		6/1989	Araki
4,889,291	A		12/1989	Goldhammer et al.
4,890,797	A		1/1990	Fujii et al.
4,914,721	A		4/1990	Glaeser
5,017,972	A		5/1991	Daughton
5,081,406	A		1/1992	Hughes et al.
5,139,205	A		8/1992	Gallagher et al.
5,166,406	A		11/1992	Vranish
5,166,679	A		11/1992	Vranish et al.
5,167,374	A		12/1992	Strohmeyer
5,186,398	A		2/1993	Vigneau, Jr.
5,198,777	A		3/1993	Masuda et al.
5,342,033	A		8/1994	Iwata
5,345,138	A		9/1994	Mukaidono et al.
5,353,468	A		10/1994	Yap
5,397,890	A		3/1995	Schueler et al.
5,409,171	A		4/1995	Stangenberg et al.
5,415,355	A		5/1995	Gollwitzer
5,429,313	A		7/1995	Schwelling
5,453,644	A		9/1995	Yap
5,494,229	A		2/1996	Rokos
5,539,322	A		7/1996	Zoughi et al.
5,662,280	A		9/1997	Nishio et al.
5,743,521	A		4/1998	Munakata et al.
5,772,129	A		6/1998	Nishio et al.
5,775,605	A		7/1998	Tsai
5,823,529	A		10/1998	Mandel
5,850,342	A		12/1998	Nakamura et al.
5,871,162	A		2/1999	Rajewski
5,924,637	A		7/1999	Niederholtmeyer
D412,716	S		8/1999	Kroger
5,942,975	A		8/1999	Sorenson
D414,198	S		9/1999	Iwata
5,988,542	A		11/1999	Henreckson
6,065,696	A		5/2000	Tsai
D426,805	S		6/2000	Iwata
6,079,645	A		6/2000	Henreckson et al.
6,116,528	A		9/2000	Schwelling
6,141,883	A		11/2000	Mitchell et al.
6,265,682	B1		7/2001	Lee
6,376,939	B1		4/2002	Suzuki et al.
6,418,004	B1		7/2002	Mather et al.
6,518,497	B1	*	2/2003	Allaire et al. ..... 174/40 R
6,550,701	B1		4/2003	Chang
6,561,444	B1		5/2003	Yokomine et al.
6,601,787	B1		8/2003	Langenecker
6,655,943	B1		12/2003	Peterson
6,666,959	B2		12/2003	Uzoh et al.
6,676,460	B1		1/2004	Motsenbocker
6,698,640	B2		3/2004	Hakozaki
6,724,324	B1		4/2004	Lambert
6,802,465	B1		10/2004	Norcott et al.
6,813,983	B2		11/2004	Gass et al.
6,826,988	B2		12/2004	Gass
6,857,345	B2		2/2005	Gass
6,877,410	B2		4/2005	Gass et al.
6,880,440	B2		5/2005	Gass et al.
6,920,814	B2		7/2005	Gass et al.
6,979,813	B2		12/2005	Avril
6,983,903	B2		1/2006	Chang
6,997,408	B2		2/2006	Watano
7,025,293	B2		4/2006	Matlin et al.
7,040,559	B2		5/2006	Matlin
7,166,561	B2		1/2007	Allen
7,210,867	B1	*	5/2007	Silverbrook 400/58
7,213,780	B2		5/2007	Chen
7,311,276	B2		12/2007	Matlin et al.
7,490,786	B2		2/2009	Matlin et al.
7,520,452	B2		4/2009	Watano et al.
7,584,545	B2		9/2009	Pan et al.
7,624,938	B2		12/2009	Aries et al.
7,631,822	B2		12/2009	Matlin et al.
7,631,823	B2		12/2009	Matlin et al.
7,631,824	B2		12/2009	Matlin et al.
7,635,102	B2		12/2009	Matlin et al.
7,661,612	B2		2/2010	Lee et al.
7,661,614	B2		2/2010	Matlin et al.
7,663,769	B2		2/2010	Hayashihara et al.
7,712,688	B2		5/2010	Priester
7,712,689	B2		5/2010	Matlin et al.
2002/0017175	A1		2/2002	Gass et al.
2002/0017176	A1		2/2002	Gass et al.
2002/0017178	A1		2/2002	Gass et al.
2002/0017179	A1		2/2002	Gass et al.
2002/0017180	A1		2/2002	Gass et al.
2002/0017181	A1		2/2002	Gass et al.
2002/0017182	A1		2/2002	Gass et al.
2002/0017184	A1		2/2002	Gass et al.
2002/0017336	A1		2/2002	Gass et al.
2002/0020261	A1		2/2002	Gass et al.
2002/0020262	A1		2/2002	Gass et al.
2002/0020263	A1		2/2002	Gass et al.
2002/0020265	A1		2/2002	Gass et al.
2002/0020271	A1		2/2002	Gass et al.
2002/0056348	A1		5/2002	Gass et al.
2002/0056349	A1		5/2002	Gass et al.
2002/0056350	A1		5/2002	Gass et al.
2002/0059853	A1		5/2002	Gass et al.
2002/0059854	A1		5/2002	Gass et al.
2002/0059855	A1		5/2002	Gass et al.
2002/0066346	A1		6/2002	Gass et al.
2002/0069734	A1		6/2002	Gass et al.
2002/0170399	A1		11/2002	Gass et al.
2002/0170400	A1		11/2002	Gass
2002/0190581	A1		12/2002	Gass et al.
2003/0002942	A1		1/2003	Gass et al.
2003/0005588	A1		1/2003	Gass et al.
2003/0015253	A1		1/2003	Gass et al.
2003/0016365	A1	*	1/2003	Liess et al. 356/498
2003/0019341	A1		1/2003	Gass et al.
2003/0020336	A1		1/2003	Gass et al.
2003/0037651	A1		2/2003	Gass et al.
2003/0042342	A1		3/2003	Kroger et al.
2003/0056853	A1		3/2003	Gass et al.
2003/0058121	A1		3/2003	Gass et al.
2003/0090224	A1		5/2003	Gass et al.
2003/0131703	A1		7/2003	Gass et al.
2003/0140749	A1		7/2003	Gass et al.
2003/0196824	A1		10/2003	Gass et al.
2004/0008122	A1		1/2004	Michael
2004/0040426	A1		3/2004	Gass et al.
2004/0069883	A1		4/2004	Watanabe et al.
2004/0159198	A1		8/2004	Peot et al.
2004/0163514	A1		8/2004	Gass et al.
2004/0173430	A1		9/2004	Gass
2004/0194594	A1		10/2004	Dils et al.
2004/0226800	A1		11/2004	Pierga
2005/0039586	A1		2/2005	Gass et al.
2005/0039822	A1		2/2005	Gass et al.
2005/0041359	A1		2/2005	Gass
2005/0046651	A1	*	3/2005	Askren et al. 347/12
2005/0066784	A1		3/2005	Gass
2005/0103510	A1		5/2005	Gass et al.
2005/0139051	A1		6/2005	Gass et al.
2005/0139056	A1		6/2005	Gass et al.
2005/0139057	A1		6/2005	Gass et al.
2005/0139058	A1		6/2005	Gass et al.
2005/0139459	A1		6/2005	Gass et al.
2005/0150986	A1		7/2005	Castronovo
2005/0155473	A1		7/2005	Gass
2005/0166736	A1		8/2005	Gass et al.
2005/0213106	A1	*	9/2005	Weijers et al. 356/519

2006/0016919	A1	1/2006	Castronovo	
2006/0054725	A1	3/2006	Matlin	
2006/0091247	A1	5/2006	Matlin	
2006/0243631	A1	11/2006	Duke	
2007/0007373	A1	1/2007	Matlin	
2007/0025239	A1	2/2007	Jain et al.	
2007/0063082	A1	3/2007	Coleman	
2007/0080252	A1	4/2007	Pierce	
2007/0087942	A1	4/2007	Allen	
2007/0164135	A1	7/2007	Zhong	
2007/0164138	A1	7/2007	Allen	
2007/0215728	A1	9/2007	Priester	
2007/0221767	A1	9/2007	Matlin et al.	
2008/0093487	A1	4/2008	Lee	
2008/0231261	A1	9/2008	Dengler et al.	
2009/0025239	A1	1/2009	Pan	
2009/0032629	A1	2/2009	Aries et al.	
2009/0090797	A1	4/2009	Matlin et al.	
2010/0051731	A1	3/2010	Matlin et al.	
2010/0084496	A1	4/2010	Matlin et al.	
2010/0102153	A1	4/2010	Matlin et al.	
2010/0134805	A1	6/2010	Pan	
2010/0170967	A1	7/2010	Jensen et al.	
2010/0170969	A1	7/2010	Jensen et al.	
2010/0176227	A1	7/2010	Davis et al.	
2010/0181398	A1	7/2010	Davis et al.	
2010/0213296	A1	8/2010	Sued et al.	
2010/0213297	A1	8/2010	Sued et al.	
2010/0213300	A1	8/2010	Matlin et al.	
2010/0243774	A1	9/2010	Hu et al.	
2010/0252661	A1	10/2010	Matlin et al.	
2010/0252664	A1	10/2010	Matlin et al.	
2010/0270404	A1	10/2010	Chen	
2010/0282879	A1	11/2010	Chen	
2010/0288861	A1	11/2010	Cai et al.	
2010/0320297	A1	12/2010	Matlin et al.	
2010/0320299	A1	12/2010	Matlin et al.	
2011/0272504	A1	11/2011	Matlin et al.	
2011/0272505	A1	11/2011	Matlin et al.	
2011/0280642	A1 *	11/2011	Ikeda et al.	400/582
2011/0297769	A1	12/2011	Matlin et al.	
2011/0297770	A1	12/2011	Matlin et al.	

FOREIGN PATENT DOCUMENTS

DE	4121330		1/1993
DE	4207292		1/1993
DE	4237861		5/1994
DE	4437348		4/1996
DE	19835093		2/1999
DE	202004000907		5/2005
DE	102006036136		1/2008
DE	202010001577	U1	11/2010
EP	268244		11/1987
EP	0392867		10/1990
EP	562076		9/1992
EP	524708		1/1997
EP	0792691		9/1997
EP	0818241		1/1998
EP	856945		1/1998
EP	855 221	A	7/1998
EP	855221		7/1998
EP	1177832		2/2002
EP	1195202		4/2002
EP	2180290		7/2008
EP	2022566		2/2009
GB	1199903		7/1970
GB	2171029		8/1986
GB	2209963		6/1989
GB	1199903		7/1990
GB	2 440 651	A	2/2008
GB	2440651		2/2008
GB	2442942		4/2008
GB	2451513		2/2009
JP	52-11691		1/1977
JP	5311911		3/1978
JP	57-76734		1/1980
JP	57-070445 (U)		4/1982
JP	57-76734		5/1982
JP	58-223448		12/1983
JP	59150554		8/1984
JP	61-000702		1/1986
JP	62183555		11/1987
JP	63-173342		11/1988
JP	2-277560		11/1990
JP	H2-303550		12/1990
JP	04-157093		5/1992
JP	04-0180852		6/1992
JP	5-96198		4/1993
JP	H05-092144		4/1993
JP	6-277548		10/1994
JP	7-299377		11/1995
JP	8-108088		4/1996
JP	8-131861		5/1996
JP	08-131962		5/1996
JP	08-164343		6/1996
JP	9-38513		2/1997
JP	09075763		3/1997
JP	09-150069		10/1997
JP	9-262491		10/1997
JP	10-048344		2/1998
JP	11-216383		8/1999
JP	11-304942		11/1999
JP	2000346288		12/2000
JP	2002-239405		8/2002
JP	2004-321840		11/2004
JP	2004321993		11/2004
WO	2005070553		8/2005
WO	2006019985		2/2006
WO	2006036370		4/2006
WO	2007/109753	A2	9/2007
WO	2007109753		9/2007
WO	2007122364		11/2007
WO	2007137761		12/2007

OTHER PUBLICATIONS

Complaint for Declaratory Judgment filed on Nov. 15, 2010 by Royal Applicance Manufacturing Co., d/b/a/ TTI Floor Care North America and Techtronic Industries Co. Ltd. against Fellowes, Inc.

First Amended Complaint filed on Aug. 19, 2011 by Fellowes, Inc., in the case of *Fellowes, Inc.* v. *ACCO Brands Corp., et al.* (Northern District of Illinois Civil Action No. 1:11-cv-04229).

Answer to First Amended Complaint filed on Sep. 6, 2011 by ACCO Brands Corporation, in the case of *Fellowes, Inc.* v. *ACCO Brands Corp., et al.* (Northern District of Illinois Civil Action No. 1:11-cv-04229).

Plaintiff's Initial Invalidity Contentions filed on Sep. 12, 2011 by Royal Appliance Manufacturing Co., in the case of *Royal Appliance Manufacturing Co., d/b/a TTI Floor Care North America and Techtronic Industries Co., Ltd.* v. *Fellowes, Inc.*, filed in the Northern District of Ohio (Case No. 1:10-cv-2604).

Defendant's Initial Validity Contentions filed on Oct. 3, 2011 by Fellowes, Inc., in the case of *Royal Appliance Manufacturing Co., d/b/a TTI Floor Care North America and Techtronic Industries Co., Ltd.* v. *Fellowes, Inc.*, filed in the Northern District of Ohio (Case No. 1:10-cv-2604).

Plaintiff's Initial Noninfringement Contentions filed on Sep. 12, 2011 by Royal Appliance Manufacturing Co., in the case of *Royal Appliance Manufacturing Co., d/b/a TTI Floor Care North America and Techtronic Industries Co., Ltd.* v. *Fellowes, Inc.*, filed in the Northern District of Ohio (Case No. 1:10-cv-2604).

Fellowes' Initial Validity Contentions filed on Oct. 26, 2011 by Fellowes, Inc., in the case of *Royal Appliance Manufacturing Co., d/b/a TTI Floor Care North America and Techtronic Industries Co., Ltd.* v. *Fellowes, Inc.*, filed in the Northern District of Ohio (Case No. 1:10-cv-2604).

Plaintiff's Preliminary Invalidity and Unenforceability Contentions filed on Sep. 2, 2011 by Royal Appliance Manufacturing Co., in the case of *Royal Appliance Manufacturing Co., d/b/a TTI Floor Care North America, et al.* v. *Fellowes, Inc.*, filed in the Northern District of Ohio (Case No. 1:11 CV 01276).

Defendant's Validity and Enforceability Contentions filed on Sep. 26, 2011 by Fellowes, Inc., in the case of *Royal Appliance Manufacturing Co., d/b/a TTI Floor Care North America, et al.* v. *Fellowes, Inc.*, filed in the Northern District of Ohio (Case No. 1:11 CV 01276).

GBC Shredmaster Service Manual, Part #6001054, referencing Models 2230S and 2250X Paper Shredders, Nov. 1997.
ACCO Rexel, Mainstream 1050/2150/2250/3150/3250 and 3350, 115V Machines Illustrated Parts Lists and Services Instructions, Mar. 25, 2002, Issue No. 4.
ACCO Rexel, Deckside and Office 115V Machines Illustrated Parts Lists and Service Instructions, Aug. 18, 1999.
ACCO Rexel, Deckside and Office 230V Machines Illustrated Parts Lists and Service Instructions, Aug. 1, 2000.
U.S. Appl. No. 60/613,750, filed Sep. 27, 2004, Pierce.
U.S. Appl. No. 60/686,490, filed May 31, 2005, Pierce.
U.S. Appl. No. 60/688,285, filed Jun. 7, 2005, Pierce.
The Stationary and Business Machines—Japan, "DS-4000 by Carl Jimuki K.K.", Jun. 2003.
The Stationary and Business Machines—Japan, "NSE-501CN by Nakabayashi K.K.", Oct. 2004.
Plaintiffs' Opening Claim Construction Brief filed on Jun. 1, 2012 by Royal Appliance Manufacturing Co., in the case of *Royal Appliance Manufacturing Co., d/b/a TTI Floor Care North America and Techtronic Industries Co., Ltd.* v. *Fellowes, Inc.,* filed in the Northern District of Ohio (Case No. 1:10-cv-2604).
Defendant's Opening Claim Construction Brief filed on Jun. 1, 2012 by Fellowes, Inc., in the case of *Royal Appliance Manufacturing Co., d/b/a TTI Floor Care North America and Techtronic Industries Co., Ltd.* v. *Fellowes, Inc.,* filed in the Northern District of Ohio (Case Nos. 1:10-cv-2604, 11-cv-1276, 11-cv-2617 and 12-cv-23).
Request for Inter Partes Reexamination As Filed in the U.S. Patent and Trademark Office on Aug. 23, 2011, regarding U.S. Patent No. 7,963,468.
Correction Document Containing Replacement Explanation Filed in Response to Notice of Failure to Comply with Inter Partes Reexamination Request Filing Requirements as filed in the U.S. Patent and Trademark Office on Sep. 2, 2011, regarding U.S. Appl. No. 95/001,723 (Patent No. 7,963,468).
Order Granting Request for Inter Partes Reexamination with an Office Action regarding U.S. Appl. No. 95/001,723 (Patent No. 7,963,468), issued by the U.S. Patent and Trademark Office on Nov. 10, 2011.
Office Action for Inter Partes Reexamination regarding U.S. Appl. No. 95/001,723 (Patent No. 7,963,468), issued by the U.S. Patent and Trademark Office on Nov. 10, 2011.
Patentee Response to Office Action in Inter Partes Reexamination as filed in the U.S. Patent and Trademark Office on Jan. 10, 2012, regarding U.S. Appl. No. 95/001,723 (Patent No. 7,963,468).
Requester's Comments on Patentee's Response to Office Action as filed in the U.S. Patent and Trademark Office on Feb. 8, 2012, regarding U.S. Appl. No. 95/001,723 (Patent No. 7,963,468).
Action Closing Prosecution regarding U.S. Appl. No. 95/001,723 (Patent No. 7,963,468), issued by the U.S. Patent and Trademark Office on May 8, 2012.
Patentee Response to Office Action in Inter Partes Reexamination as filed in the U.S. Patent and Trademark Office on May 14, 2012, regarding U.S. Appl. No. 95/001,723 (Patent No. 7,963,468).
Request for Inter Partes Reexamination As Filed in the U.S. Patent and Trademark Office on Sep. 2, 2011, regarding U.S. Patent No. 7,631,822.
Order Granting Request for Inter Partes Reexamination regarding U.S. Appl. No. 95/001,736 (Patent No. 7,631,822), issued by the U.S. Patent and Trademark Office on Oct. 26, 2011.
Office Action in Inter Partes Reexamination regarding U.S. Appl. No. 95/001,736 (Patent No. 7,631,822), issued by the U.S. Patent and Trademark Office on Nov. 10, 2011.
Partial International Search Report issued with Invitation to Pay Additional Fees issued in PCT/US2008/078458, Jan. 26, 2009, 2 pages.
International Search Report (PCT/ISA/210) issued in PCT/US2007/0064601, mailed Feb. 8, 2008, 5 pages.
Written Opinion of the International Searching Authority (PCT/ISA/237) issued in PCT/US2007/0064601, mailed Feb. 8, 2008, 16 pages.
English Abstract of German patent application No. DE 1020006036136 of Erlecke, published Jan. 31, 2008.
TI's Digital Signal Controllers Put Brake On SawStop Table Saw, Feb. 9, 2005, pp. 1-3 (printed from www.embeddedstar.com/press/content/2005/2/embedded17827.html).
European Search Report issued in EP 08 17 0857, Feb. 10, 2009, 6 pages.
International Search Report for PCT/US2006/000010 dated May 11, 2006.
European Search Report issued in Application No. 08102126.3, May 19, 2008, 5 pages.
Manual Translation of Japanese application 2004-321993, published Nov. 18, 2004.
Manual Translation of Japanese application 2002-239405, published Aug. 27, 2002.
Invitation to Pay Additional Fees with Partial International Search Report in PCT/US2007/064601, Sep. 12, 2007, 8 pages.

* cited by examiner



FIG. 1


48
44
14
50
36
24
52
54
46
42
10
26
28
29
27
16
21
23
18
32
61
64
68
66
30
64
61
66
68
62
60
12

FIG. 2



FIG. 3



FIG. 4



FIG. 5


100
THICKNESS DETECTOR
200
SHREDDER CONTROLLER
96
LUBRICATION SYSTEM CONTROLLER
MEMORY
97
110
INDICATOR
16
SHREDDER MECHANISM
82
PUMP

FIG. 6


110
116
RED
YELLOW
114
YELLOW
114
YELLOW
114
YELLOW
114
GREEN
112

FIG. 7


36
100
120
122
16
19
19
20
20

FIG. 8


36
100
120
126
132
124
128
134
130
16
19
19
20
20

FIG. 9



FIG. 10



FIG 11


300
302
START
304
INSERT ITEM TO BE SHREDDED INTO THROAT
306
DETECT THICKNESS OF ITEM
308
IS THICKNESS AT LEAST A PREDETERMINED MAXIMUM THICKNESS?
Y
310
PROVIDE WARNING
312
REMOVE ITEM FROM THROAT
314
REDUCE THICKNESS OF ITEM
N
316
SHRED ITEM
318
INSERT ADDITIONAL ITEM?
Y
N
320
END

FIG. 12

SHREDDER WITH THICKNESS DETECTOR

Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of and claims priority to U.S. patent application Ser. No. 11/177,480, filed on Jul. 11, 2005 and [currently pending] *now U.S. Pat. No. 7,661,614*, the entire contents of which is incorporated herein by reference. This application is also a continuation-in-part of and claims priority to U.S. patent application Ser. No. 11/385,864, filed on Mar. 22, 2006 and [currently pending] *now U.S. Pat. No. 7,798,435*, the entire content of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to shredders for destroying articles, such as documents, compact discs, etc.

2. Description of Related Art

Shredders are well known devices for destroying articles, such as documents, compact discs ("CDs"), expired credit cards, etc. Typically, users purchase shredders to destroy sensitive articles, such as credit card statements with account information, documents containing company trade secrets, etc.

A common type of shredder has a shredder mechanism contained within a housing that is removably mounted atop a container. The shredder mechanism typically has a series of cutter elements that shred articles fed therein and discharge the shredded articles downwardly into the container. The shredder typically has a stated capacity, such as the number of sheets of paper (typically of 20 lb. weight) that may be shredded at one time; however, the feed throat of a typical shredder can receive more sheets of paper than the stated capacity. A common frustration of users of shredders is to feed too many papers into the feed throat, only to have the shredder jam after it has started to shred the papers. To free the shredder of the papers, the user typically reverses the direction of rotation of the cutter elements via a switch until the papers become free.

In addition, shredders that are subjected to a lot of use should have periodic maintenance done to them. For example, the cutter elements may become dull over time. It has been found that lubricating the cutter elements may improve the performance of cutter elements, particularly if the shredder is used constantly over a long period of time.

The present invention endeavors to provide various improvements over known shredders.

BRIEF SUMMARY OF THE INVENTION

It is an aspect of the invention to provide a shredder that does not jam as a result of too many papers, or an article that is too thick, being fed into the shredder.

In an embodiment, a shredder is provided. The shredder includes a housing having a throat for receiving at least one article to be shredded, and a shredder mechanism received in the housing. The shredder mechanism includes an electrically powered motor and cutter elements. The shredder mechanism enables the at least one article to be shredded to be fed into the cutter elements. The motor is operable to drive the cutter elements so that the cutter elements shred the articles fed therein. The shredder also includes a detector that is configured to detect a thickness of the at least one article being received by the throat, and a controller that is operable to perform a predetermined operation responsive to the detector detecting that the thickness of the at least one article is at least equal to a predetermined maximum thickness.

In an embodiment, a method for operating a shredder is provided. The method includes detecting a thickness of at least one article being inserted into a throat of the shredder, determining if the thickness of the at least one article is greater than a predetermined maximum thickness, and performing a predetermined operation if the detected thickness is at least equal to the predetermined maximum thickness.

It is also an aspect of the present invention to provide a shredder that automatically conducts self-maintenance after a predetermined amount of use.

In an embodiment, a shredder that includes a housing that has a throat for receiving at least one article to be shredded, and a shredder mechanism that is received in the housing is provided. The shredder mechanism includes an electrically powered motor and cutter elements. The shredder mechanism enables the at least one article to be shredded to be fed into the cutter elements and the motor being operable to drive the cutter elements so that the cutter elements shred the articles fed therein. The shredder also includes a lubrication system configured to lubricate the cutter elements, and a detector configured to detect a thickness of the at least one article being received by the throat. The shredder further includes a controller that is operable to store an accumulation of thicknesses detected by the detector over time and to provide a signal to the lubrication system to lubricate the cutter elements when the accumulation is at least equal to a predetermined total thickness.

In an embodiment, a shredder is provided. The shredder includes a housing having a throat for receiving at least one article to be shredded, and a shredder mechanism that is received in the housing. The shredder mechanism includes an electrically powered motor and cutter elements. The shredder mechanism enables the at least one article to be shredded to be fed into the cutter elements. The motor is operable to drive the cutter elements so that the cutter elements shred the articles fed therein. The shredder also includes a controller that includes a memory. The controller is operable to store information in the memory related to an amount of use of the shredder, and to alert a user of the shredder when the shredder is due for a maintenance operation, based on the amount of use of the shredder.

Other aspects, features, and advantages of the present invention will become apparent from the following detailed description, the accompanying drawings, and the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** is a perspective view of a shredder constructed in accordance with an embodiment of the present invention;

FIG. **2** is an exploded perspective view of the shredder of FIG. **1**;

FIG. **3** is a schematic illustration of an oiling mechanism in accordance with an embodiment of the present invention;

FIG. **4** is a perspective view of a shredder having an oiling mechanism in accordance with an embodiment of the present invention;

FIG. **5** is a perspective view of a shredder having an oiling mechanism in accordance with an embodiment of the present invention;

FIG. **6** is a schematic of interaction between a controller and other parts of the shredder;

FIG. **7** is a schematic of an embodiment of an indicator located on the shredder;

FIG. **8** is a schematic of an embodiment of a detector configured to detect a thickness of a article to be shredded by the shredder;

FIG. **9** is a schematic of another embodiment of a detector configured to detect a thickness of a article to be shredded by the shredder;

FIG. **10** is a schematic of another embodiment of a detector configured to detect a thickness of a article to be shredded by the shredder;

FIG. **11** is a schematic of another embodiment of the detector of FIG. **10**; and

FIG. **12** is a flow diagram of an embodiment of a method for shredding an article.

DETAILED DESCRIPTION OF THE INVENTION

FIGS. **1** and **2** illustrate a shredder constructed in accordance with an embodiment of the present invention. The shredder is generally indicated at **10**. In the illustrated embodiment, the shredder **10** sits atop a waste container, generally indicated at **12**, which is formed of molded plastic or any other material. The shredder **10** illustrated is designed specifically for use with the container **12**, as the shredder housing **14** sits on the upper periphery of the waste container **12** in a nested relation. However, the shredder **10** may also be designed so as to sit atop a wide variety of standard waste containers, and the shredder **10** would not be sold with the container. Likewise, the shredder **10** could be part of a large freestanding housing, and a waste container would be enclosed in the housing. An access door would provide for access to and removal of the container. Generally speaking, the shredder **10** may have any suitable construction or configuration and the illustrated embodiment is not intended to be limiting in any way. In addition, the term "shredder" is not intended to be limited to devices that literally "shred" documents and articles, but is instead intended to cover any device that destroys documents and articles in a manner that leaves each document or article illegible and/or useless.

As shown in FIG. **2**, in an embodiment, the shredder **10** includes a shredder mechanism **16** that includes an electrically powered motor **18** and a plurality of cutter elements **19**. "Shredder mechanism" is a generic structural term to denote a device that destroys articles using at least one cutter element. Such destroying may be done in any particular way. For example, the shredder mechanism may include at least one cutter element that is configured to punch a plurality of holes in the document or article in a manner that destroys the document or article. In the illustrated embodiment, the cutter elements **19** are generally mounted on a pair of parallel rotating shafts **20**. The motor **18** operates using electrical power to rotatably drive the shafts and the cutter elements through a conventional transmission **23** so that the cutter elements shred articles fed therein. The shredder mechanism **16** may also include a sub-frame **21** for mounting the shafts, the motor **18**, and the transmission **23**. The operation and construction of such a shredder mechanism **16** are well known and need not be described herein in detail. Generally, any suitable shredder mechanism **16** known in the art or developed hereafter may be used.

The shredder **10** also includes the shredder housing **14**, mentioned above. The shredder housing **14** includes top wall **24** that sits atop the container **12**. The top wall **24** is molded from plastic and an opening **26** is located at a front portion thereof. The opening **26** is formed in part by a downwardly depending generally U-shaped member **28**. The U-shaped member **28** has a pair of spaced apart connector portions **27** on opposing sides thereof and a hand grip portion **28** extending between the connector portions **27** in spaced apart relation from the housing **14**. The opening **26** allows waste to be discarded into the container **12** without being passed through the shredder mechanism **16**, and the member **28** may act as a handle for carrying the shredder **10** separate from the container **12**. As an optional feature, this opening **26** may be provided with a lid, such as a pivoting lid, that opens and closes the opening **26**. However, this opening in general is optional and may be omitted entirely. Moreover, the shredder housing **14** and its top wall **24** may have any suitable construction or configuration.

The shredder housing **14** also includes a bottom receptacle **30** having a bottom wall, four side walls and an open top. The shredder mechanism **16** is received therein, and the receptacle **30** is affixed to the underside of the top wall **24** by fasteners. The receptacle **30** has an opening **32** in its bottom wall through which the shredder mechanism **16** discharges shredded articles into the container **12**.

The top wall **24** has a generally laterally extending opening, which is often referred to as a throat **36**, extending generally parallel and above the cutter elements. The throat **36** enables the articles being shredded to be fed into the cutter elements. As can be appreciated, the throat **36** is relatively narrow, which is desirable for preventing overly thick items, such as large stacks of documents, from being fed into cutter elements, which could lead to jamming. The throat **36** may have any configuration.

The top wall **24** also has a switch recess **38** with an opening therethrough. An on/off switch **42** includes a switch module (not shown) mounted to the top wall **24** underneath the recess **38** by fasteners, and a manually engageable portion **46** that moves laterally within the recess **38**. The switch module has a movable element (not shown) that connects to the manually engageable portion **46** through the opening. This enables movement of the manually engageable portion **46** to move the switch module between its states.

In the illustrated embodiment, the switch module connects the motor **18** to the power supply. Typically, the power supply will be a standard power cord **44** with a plug **48** on its end that plugs into a standard AC outlet. The switch **42** is movable between an on position and an off position by moving the portion **46** laterally within the recess **38**. In the on position, contacts in the switch module are closed by movement of the manually engageable portion **46** and the movable element to enable a delivery of electrical power to the motor **18**. In the off position, contacts in the switch module are opened to disable the delivery of electric power to the motor **18**.

As an option, the switch **42** may also have a reverse position wherein contacts are closed to enable delivery of electrical power to operate the motor **18** in a reverse manner. This would be done by using a reversible motor and applying a current that is of a reverse polarity relative to the on position. The capability to operate the motor **18** in a reversing manner is desirable to move the cutter elements in a reversing direction for clearing jams. In the illustrated embodiment, in the off position the manually engageable portion **46** and the movable element would be located generally in the center of the recess **38**, and the on and reverse positions would be on opposing lateral sides of the off position.

Generally, the construction and operation of the switch **42** for controlling the motor **42** are well known and any construction for such a switch **42** may be used.

In the illustrated embodiment, the top cover **24** also includes another recess **50** associated with an optional switch lock **52**. The switch lock **52** includes a manually engageable portion **54** that is movable by a user's hand and a locking portion (not shown). The manually engageable portion **54** is seated in the recess **50** and the locking portion is located beneath the top wall **24**. The locking portion is integrally formed as a plastic piece with the manually engageable portion **54** and extends beneath the top wall **24** via an opening formed in the recess **50**.

The switch lock **52** causes the switch **42** to move from either its on position or reverse position to its off position by a camming action as the switch lock **52** is moved from a releasing position to a locking position. In the releasing position, the locking portion is disengaged from the movable element of the switch **42**, thus enabling the switch **42** to be moved between its on, off, and reverse positions. In the locking position, the movable element of the switch **42** is restrained in its off position against movement to either its on or reverse position by the locking portion of the switch lock **52**.

Preferably, but not necessarily, the manually engageable portion **54** of the switch lock **52** has an upwardly extending projection **56** for facilitating movement of the switch lock **52** between the locking and releasing positions.

One advantage of the switch lock **52** is that, by holding the switch **42** in the off position, to activate the shredder mechanism **16** the switch lock **52** must first be moved to its releasing position, and then the switch **42** is moved to its on or reverse position. This reduces the likelihood of the shredder mechanism **16** being activated unintentionally. Reference may be made to U.S. Patent Application Publication No. 2005-0218250 A1, which is incorporated herein by reference, for further details of the switch lock **52**. This switch lock is an entirely optional feature and may be omitted.

In the illustrated embodiment, the shredder housing **14** is designed specifically for use with the container **12** and it is intended to sell them together. The upper peripheral edge **60** of the container **12** defines an upwardly facing opening **62**, and provides a seat **61** on which the shredder **10** is removably mounted. The seat **61** includes a pair of pivot guides **64** provided on opposing lateral sides thereof. The pivot guides **64** include upwardly facing recesses **66** that are defined by walls extending laterally outwardly from the upper edge **60** of the container **12**. The walls defining the recesses **66** are molded integrally from plastic with the container **12**, but may be provided as separate structures and formed from any other material. At the bottom of each recess **66** is provided a step down or ledge providing a generally vertical engagement surface **68**. This step down or ledge is created by two sections of the recesses **66** being provided with different radii. Reference may be made to U.S. Pat. No. 7,025,293, which is incorporated herein by reference, for further details of the pivotal mounting. This pivotal mounting is entirely optional and may be omitted.

As schematically illustrated in FIG. **3**, in order to lubricate the cutter elements **19** of the shredder **10**, a lubrication system **80** may be included for providing lubrication at the cutter elements **19**. The system includes a pump **82**, that draws lubricating fluid, such as oil, from a reservoir **84**. In a typical application, the reservoir **84** will have a fill neck **86** that extends through the top wall **24** of the shredder housing **14** to allow for easy access for refilling the reservoir (see FIG. **5**).

The pump **82** communicates through a series of conduits **88** to one or more nozzles **90** that are positioned proximate the cutter elements **19**. In one embodiment, the nozzles can be positioned such that oil forced through the nozzles is dispersed as sprayed droplets in the throat of the shredder **10**. In another embodiment, the oil is dispersed in back of the throat of the shredder **10**. Generally, the nozzles have openings small relative to the conduits, thereby creating a high speed flow at the nozzle, allowing the oil to be expelled at a predictable rate and pattern.

As shown in FIG. **4**, a system in accordance with an embodiment of the present invention may be a retrofit device. In this embodiment, the reservoir **84** is mounted to an outside surface of the shredder **10**. It is connected via a conduit **92** to the main unit **94**. The main unit **94** may include a power supply (not shown) and the pump **82** (not shown in FIG. **4**). In any embodiment, the reservoir **84** may be designed to be removed and replaced, rather than re-filled.

An alternate embodiment includes the system **80** built into the housing of the shredder **10**. In this embodiment, shown in FIG. **5**, the fill neck **86** can be designed to extend through the top wall **24** of the shredder housing **14**. Operation of the system **80** does not depend on whether it is retrofit or built-in.

In operation, a controller **96** (shown in FIG. **6**) for the lubrication system **80** is programmed with instructions for determining when to lubricate the cutter elements **19**. The controller processes the instructions and subsequently applies them by activating the pump **82** to cause fluid from the reservoir to be delivered to the nozzles **90** under pressure. The nozzles are positioned and arranged to spray the pressurized lubricating oil to the cutter elements **19**. In general, the oil will be dispersed in a predetermined pattern directly onto the cutter elements and/or the strippers. In a particular arrangement, it may be useful to array the nozzles below the cutter elements so that lubrication is sprayed from below. In an alternate embodiment, the oil is sprayed onto an intermediate surface **98** (shown in FIG. **3**) and allowed to drip from there onto the cutter elements **19** and the strippers (which are generally located on the outward or post-cutting side of the cutting mechanism and include a serrated member or a comb type member having teeth that protrude into the spaces between the individual cutting disks). The illustrated embodiments of the lubrication system **80** are not intended to be limiting in any way. Reference may be made to U.S. patent application Ser. No. 11/385,864, which is hereby incorporated by reference, for further details of an oiling mechanism. The lubrication system **80** is an optional feature of the shredder **10**.

In an embodiment of the invention, the shredder **10** includes a thickness detector **100** to detect overly thick stacks of documents or other articles that could jam the shredder mechanism **16**, and communicate such detection to a controller **200**, as shown in FIG. **6**. Upon such detection, the controller **200** may communicate with an indicator **110** that provides a warning signal to the user, such as an audible signal and/or a visual signal. Examples of audible signals include, but are not limited to beeping, buzzing, and/or any other type of signal that will alert the user that the stack of documents or other article that is about to be shredded is above a predetermined maximum thickness and may cause the shredder mechanism **16** to jam. This gives the user the opportunity to reduce the thickness of the stack of documents or reconsider forcing the thick article through the shredder, knowing that any such forcing may jam and/or damage the shredder.

A visual signal may be provided in the form of a red warning light, which may be emitted from an LED. It is also contemplated that a green light may also be provided to

indicate that the shredder **10** is ready to operate. In an embodiment, the indicator **110** is a progressive indication system that includes a series of indicators in the form of lights to indicate the thickness of the stack of documents or other article relative to the capacity of the shredder is provided, as illustrated in FIG. **7**. As illustrated, the progressive indication system includes a green light **112**, a plurality of yellow lights **114**, and a red light **116**. The green light **112** indicates that the detected thickness of the item (e.g. a single paper, a stack of papers, a compact disc, a credit card, etc.) that has been placed in the throat **36** of the shredder **10** is below a first predetermined thickness and well within the capacity of the shredder. The yellow lights **114** provide a progressive indication of the thickness of the item. The first yellow light **114**, located next to the green light **112**, would be triggered when the detected thickness is at or above the first predetermined thickness, but below a second predetermined thickness that triggers the red light **116**. If there is more than one yellow light **114**, each additional yellow light **114** may correspond to thicknesses at or above a corresponding number of predetermined thicknesses between the first and second predetermined thicknesses. The yellow lights **114** may be used to train the user into getting a feel for how many documents should be shredded at one time. The red light **116** indicates that the detected thickness is at or above the second predetermined thickness, which may be the same as the predetermined maximum thickness, thereby warning the user that this thickness has been reached.

The sequence of lights may be varied and their usage may vary. For example, they may be arranged linearly in a sequence as shown, or in other configurations (e.g. in a partial circle so that they appear like a fuel gauge or speedometer. Also, for example, the yellow light(s) **114** may be lit only for thickness(es) close to (i.e., within 25% of) the predetermined maximum thickness, which triggers the red light **116**. This is a useful sequence because of most people's familiarity with traffic lights. Likewise, a plurality of green lights (or any other color) could be used to progressively indicate the detected thickness within a range. Each light would be activated upon the detected thickness being equal to or greater than a corresponding predetermined thickness. A red (or other color) light may be used at the end of the sequence of lights to emphasize that the predetermined maximum thickness has been reached or exceeded (or other ways of getting the user's attention may be used, such as emitting an audible signal, flashing all of the lights in the sequence, etc.). These alert features may be used in lieu of or in conjunction with cutting off power to the shredder mechanism upon detecting that the predetermined maximum thickness has been reached or exceeded.

Similarly, the aforementioned indicators of the progressive indicator system may be in the form of audible signals, rather than visual signals or lights. For example, like the yellow lights described above, audible signals may be used to provide a progressive indication of the thickness of the item. The audible signals may vary by number, frequency, pitch, and/or volume in such a way that provides the user with an indication of how close the detected thickness of the article is to the predetermined maximum thickness. For example, no signal or a single "beep" may be provided when the detected thickness is well below the predetermined maximum thickness, and a series of "beeps" that increase in number (e.g. more "beeps" the closer the detection is to the predetermined maximum thickness) and/or frequency (e.g. less time between beeps the closer the detection is to the predetermined maximum thickness) as the detected thickness approaches the predetermined maximum thickness may be provided. If the detected thickness is equal to or exceeds the predetermined maximum thickness, the series of "beeps" may be continuous, thereby indicating to the user that such a threshold has been met and that the thickness of the article to be shredded should be reduced.

The visual and audible signals may be used together in a single device. Also, other ways of indicating progressive thicknesses of the items inserted in the throat **36** may be used. For example, an LCD screen with a bar graph that increases as the detected thickness increases may be used. Also, a "fuel gauge," i.e., a dial with a pivoting needle moving progressively between zero and a maximum desired thickness, may also be used. As discussed above, with an audible signal, the number or frequency of the intermittent audible noises may increase along with the detected thickness. The invention is not limited to the indicators described herein, and other progressive (i.e., corresponding to multiple predetermined thickness levels) or binary (i.e., corresponding to a single predetermined thickness) indicators may be used.

The aforementioned predetermined thicknesses may be determined as follows. First, because the actual maximum thickness that the shredder mechanism may handle will depend on the material that makes up the item to be shredded, the maximum thickness may correspond to the thickness of the toughest article expected to be inserted into the shredder, such as a compact disc, which is made from polycarbonate. If it is known that the shredder mechanism may only be able to handle one compact disc at a time, the predetermined maximum thickness may be set to the standard thickness of a compact disc (i.e., 1.2 mm). It is estimated that such a thickness would also correspond to about 12 sheets of 20 lb. paper. Second, a margin for error may also be factored in. For example in the example given, the predetermined maximum thickness may be set to a higher thickness, such as to 1.5 mm, which would allow for approximately an additional 3 sheets of paper to be safely inserted into the shredder (but not an additional compact disc). Of course, these examples are not intended to be limiting in any way.

For shredders that include separate throats for receiving sheets of paper and compact discs and/or credit cards, a detector **100** may be provided to each of the throats and configured for different predetermined maximum thicknesses. For example, the same shredder mechanism may be able to handle one compact disc and 18 sheets of 20 lb. paper. Accordingly, the predetermined maximum thickness associated with the detector associated with the throat that is specifically designed to receive compact discs may be set to about 1.5 mm (0.3 mm above the standard thickness of a compact disc), while the predetermined maximum thickness associated with the detector associated with the throat that is specifically designed to receive sheets of paper may be set to about 1.8 mm. Of course, these examples are not intended to be limiting in any way and are only given to illustrate features of embodiments of the invention.

Similarly, a selector switch may optionally be provided on the shredder to allow the user to indicate what type of material is about to be shredded, and, hence the appropriate predetermined maximum thickness for the detector. A given shredder mechanism may be able to handle different maximum thicknesses for different types of materials, and the use of this selector switch allows the controller to use a different predetermined thickness for the material selected. For example, there may be a setting for "paper," "compact discs," and/or "credit cards," as these materials are known to have different cutting characteristics and are popular items to shred for security reasons. Again, based on the capacity of the shredder mechanism, the appropriate predetermined maximum thicknesses may be set based on the known thicknesses of the items

to be shredded, whether it is the thickness of a single compact disc or credit card, or the thickness of a predetermined number of sheets of paper of a known weight, such as 20 lb. The selector switch is an optional feature, and the description thereof should not be considered to be limiting in any way.

Returning to FIG. **6**, in addition to the indicator **110** discussed above, the detector **100** may also be in communication with the motor **18** that powers the shredder mechanism **16** via the controller **200**. Specifically, the controller **200** may control whether power is provided to the motor **18** so that the shafts **20** may rotate the cutter elements **19** and shred the item. This way, if the thickness of the item to be shredded is detected to be greater than the capacity of the shredder mechanism **16**, power will not be provided to the shredder mechanism **16**, thereby making the shredder **10** temporarily inoperable. This not only protects the motor **18** from overload, it also provides an additional safety feature so that items that should not be placed in the shredder **10** are not able to pass through the shredder mechanism **16**, even though they may fit in the throat **36** of the shredder **10**.

FIGS. **8-11** show different embodiments of the detector **100** that may be used to detect the thickness of an article (e.g. a compact disc, credit card, stack of papers, etc.) that is placed in the throat **36** of the shredder. As shown in FIG. **8**, the detector **100** may include a contact member **120** that is mounted so that it extends into the throat **36** at one side thereof. The contact member **120** may be pivotally mounted or it may be mounted within a slot so that it translates relative to the throat **36**. The contact member **120** is mounted so that as the item to be shredded is inserted into the throat **36**, the item engages the contact member **120** and causes the contact member **120** to be pushed out of the way of the item. As shown in FIG. **8**, a strain gauge **122** is located on a side of the contact member **120** that is opposite the throat **36**. The strain gauge **122** is positioned so that it engages the contact member **120** and is able to measure the displacement of the contact member **120** relative to the throat **36**. Other displacement sensors may be used. The greater the displacement, the thicker the item being inserted into the throat **36**. The strain gauge **122** communicates this measurement to the controller **200** and the controller **200** determines whether the displacement measured by the strain gauge **122**, and hence thickness of the item, is greater than the predetermined maximum thickness, thereby indicating that the item that is being fed into the throat of the shredder **10** will cause the shredder mechanism **16** to jam. If the detected thickness is greater than the predetermined maximum thickness, the controller **200** may send a signal to the indicator **110**, as discussed above, and/or prevent power from powering the motor **18** to drive the shafts **20** and cutter elements **19**. This way, a jam may be prevented. Likewise, the measured displacement of the contact member **120** may be used by the controller **200** to output progressive amounts of thicknesses, as discussed above. Of course, different configurations of the strain gauge **122** and contact member **120** may be used. The illustrated embodiment is not intended to be limiting in any way.

In another embodiment, illustrated in FIG. **9**, the detector **100** includes the contact member **120** and a piezoelectric sensor **124**. In this embodiment, the contact member **120** is mounted such that it protrudes through one wall **126** of the throat and into the throat by a small amount, thereby creating a slightly narrower throat opening. A spring **128** may be used to bias the contact member **120** into the throat **36**. The narrower opening that is created by a tip **130** of the contact member **120** and a wall **132** opposite the spring **128** is less than the predetermined maximum thickness. Therefore, if an item that is too thick to be shredded enters the throat **36**, it will engage a top side **134** of the contact member **120**. Because the top side **134** of the contact member **120** is sloped, the contact member **120** will move against the bias of the spring **128** and into contact with the piezoelectric sensor **124**, thereby causing a voltage to be created within the piezoelectric sensor **124**. As the thickness of the item increases, the force applied by the contact member **120** to the piezoelectric sensor **124** increases, thereby increasing the voltage generated within the piezoelectric sensor **124**. The resulting voltage may be communicated to the controller **200** or directly to the indicator **110**, thereby causing the indicator **110** to indicate that the item is above the predetermined maximum thickness. In addition, the controller, upon sensing the voltage, may prevent power from powering the motor **18** to drive the shafts **20** and cutter elements **19**. Of course, different configurations of the piezoelectric sensor **124** and contact member **120** may be used. The illustrated embodiment is not intended to be limiting in any way.

In another embodiment, illustrated in FIG. **10**, the detector **100** includes the contact member **120** and an optical sensor **140**. In this embodiment, the contact member **120** is pivotally mounted such that one portion extends into the throat **36** and another portion, which has a plurality of rotation indicators **142**, extends away from the throat **36**. The optical sensor **140** may be configured to sense the rotation indicators **142** as the rotation indicators **142** rotate past the optical sensor **140**. For example, the optical sensor **140** may include an infrared LED **144** and a dual die infrared receiver **146** to detect the direction and amount of motion of the contact member **120**. As shown in FIG. **7**, the contact member **120** may be configured such that a small amount of rotation of the contact member is amplified at the opposite end of the contact member **120**, thereby improving the sensor's ability to sense changes in the thickness of the items that cause the contact member **120** to rotate. Of course, different configurations of the optical sensor **140** and contact member **120** may be used. The illustrated embodiment is not intended to be limiting in any way.

Another embodiment of the detector **100** that includes the optical sensor **140** is shown in FIG. **11**. As illustrated in FIG. **8**, the detector **100** is located above an infrared sensor **150** that detects the presence of an article. Of course, any such sensor may be used. The illustrated embodiment is not intended to be limiting in any way. The sensor **150** provides a signal to the controller **200**, which in turn is communicated to the motor **18**. When the sensor **150** senses that an article is passing through a lower portion of the throat **36**, the controller **200** signals the motor **18** to start turning the shafts **20** and cutter elements **19**. Of course, because the detector **100** is also in communication with the controller **200**, if the detector **100** detects that the thickness of the article that has entered the throat is too thick for the capacity of the shredder mechanism **16**, the shredder mechanism **16** may not operate, even though the sensor **150** has indicated that it is time for the shredder mechanism **16** to operate. Of course, this particular configuration is not intended to be limiting in any way.

Although various illustrated embodiments herein employ particular sensors, it is to be noted that other approaches may be employed to detect the thickness of the stack of documents or article being fed into the throat **36** of the shredder **10**. For example, embodiments utilizing eddy current, inductive, photoelectric, ultrasonic, Hall effect, or even infrared proximity sensor technologies are also contemplated and are considered to be within the scope of the present invention.

The sensors discussed above, and other possible sensors, may also be used to initiate the shredding operation by enabling the power to be delivered to the motor of the shredder mechanism. This use of sensors in the shredder throat is

known, and they allow the shredder to remain idle until an item is inserted therein and contacts the sensor, which in turn enables power to operate the motor to rotate the cutting elements via the shafts. The controller **200** may be configured such that the insertion of an item will perform this function of enabling power delivery to operate the shredder mechanism motor. The motor may be cut-off or not even started if the thickness exceeds the predetermined maximum thickness.

Returning to FIG. **6**, for embodiments of the shredder **10** that include the lubrication system **80**, the controller **200** may be programmed to communicate with the controller **96** associated with the lubrication system **80** to operate the pump **82** in a number of different modes. The controller **200** and the controller **96** may be part of the same controller, or may be separate controllers that communicate with each another. In one embodiment, the controller **96** is programmed to operate according to a predetermined timing schedule. In another, the controller **96** activates the pump upon a certain number of rotations of the drive for the cutter elements. In another embodiment, the detector **100** at the throat **36** of the shredder **10** monitors the thickness of items deposited therein. Upon accumulation of a predetermined total thickness of material shredded, the controller **96** activates the pump to lubricate the cutter elements **19**. For example, if the predetermined total thickness of material is programmed in the controller **96** to be 0.1 m (100 mm), then once the total accumulated detected thickness of articles that have been shredder is at least equal to 0.1 m (e.g., one hundred articles with an average thickness of 1 mm, or fifty articles with an average thickness of 2 mm, etc.), the controller **96** will activate the pump **82** of the lubrication system **80** to lubricate the cutter elements **19**.

It is also possible to schedule the lubrication based on a number of uses of the shredder (e.g., the controller tracks or counts the number of shredding operations and activates the pump after a predetermined number of shredder operations). In each of the embodiments making use of accumulated measures, a memory **97** can be incorporated for the purpose of tracking use. Although the memory **97** is illustrated as being part of the controller **96** associated with the lubrication system, the memory may be part of the shredder controller **200**, or may be located on some other part of the shredder **10**. The illustrated embodiment is not intended to be limiting in any way.

In addition, the accumulated measures (e.g. the number of shredding operations or the accumulated thickness of the articles that have been shredded) may be used to alert the user that maintenance should be completed on the shredder. The alert may come in the form of a visual or audible signal, such as the signals discussed above, or the controller may prevent power from powering the shedder mechanism until the maintenance has been completed.

The ability to keep track of the accumulated use of the shredder may also be helpful in a warranty context, where the warranty could be based on the actual use of the shredder, rather than time. This is similar to the warranties that are used with automobiles, such as "100,000 miles or 10 years, whichever comes first." For example, the warranty may be based on 100 uses or one year, whichever comes first, or the warranty may be based on shredding paper having a total sensed thickness of 1 meter or 2 years, whichever comes first, and so on.

FIG. **12** illustrates a method **300** for detecting the thickness of an item, e.g. a stack of documents or an article, being fed into the throat **36** of the shredder **10**. The method starts at **302**. At **304**, the item is fed into the throat **36** of the shredder **10**. At **306**, the detector **100** detects the thickness of the item. At **308**, the controller **200** determines whether the thickness that has been detected is greater than a predetermined maximum thickness. The predetermined maximum thickness may be based on the capacity of the shredder mechanism **16**, as discussed above. If the controller **200** determines that the thickness that has been detected is at least the predetermined maximum thickness, at **310**, a warning is provided. For example, to provide the warning, the controller **200** may cause the red light **116** to illuminate and/or causes an audible signal to sound and/or cause power to be disrupted to the motor **18** so that the shredder mechanism **16** will not shred the item. The user should then remove the item from the throat **36** of the shredder **10** at **312**, and reduce the thickness of the item at **314** before inserting the item back into the throat **36** at **304**.

If the controller **200** determines that the thickness that has been detected is less than the predetermined maximum thickness, the controller **200** may cause the green light **112** to illuminate and/or allows power to be supplied to the shredder mechanism **16** so that the shredder **10** may proceed with shredding the item at **316**.

In the embodiment that includes the plurality of yellow lights **114** as part of the indicator **100**, if the controller **200** determines that the thickness that has been detected is less than the predetermined maximum thickness, but close to or about the predetermined maximum thickness, the controller **200** may cause one of the yellow lights to illuminate, depending on how close to the predetermined maximum thickness the detected thickness is. For example, the different yellow lights may represent increments of about 0.1 mm so that if the detected thickness is within 0.1 mm of the predetermined maximum thickness, the yellow light **114** that is closest to the red light **116** illuminates, and so on. Although power will still be supplied to the shredder mechanism **16**, the user will be warned that that particular thickness is very close to the capacity limit of the shredder **10**. Of course, any increment of thickness may be used to cause a particular yellow light to illuminate. The example given should not be considered to be limiting in any way.

Returning to the method **300** of FIG. **9**, at **318**, the user may insert an additional item, such as another document or stack of documents, as the shredder mechanism **16** is shredding the previous item that was fed into the throat **36** of the shredder at **304**. If the user does insert an additional item into the throat **36** at **318**, the method returns to **304**, and the detector **100** detects the thickness of the item at the location of the detector **100** at **306**, and so on. If part of the previous item is still in the throat **36**, the cumulative thickness of the item being shredder and the new item may be detected. If the user does not add an additional item at **318**, the method ends at **320**. The illustrated method is not intended to be limiting in any way.

The foregoing illustrated embodiments have been provided to illustrate the structural and functional principles of the present invention and are not intended to be limiting. To the contrary, the present invention is intended to encompass all modifications, alterations and substitutions within the spirit and scope of the appended claims.

What is claimed is:

[1. A shredder comprising:

a housing having a throat open to an exterior of the housing for permitting a user to feed at least one article to be shredded;

a shredder mechanism received in the housing and including an electrically powered motor and cutter elements, the shredder mechanism enabling the at least one article fed into the throat to be shredded to be fed into the cutter elements and the motor being operable to drive the cutter elements in a shredding direction so that the cutter elements shred the articles fed therein;

a thickness detector configured to detect a thickness between opposing major surfaces of the at least one article to be shredded being received by the throat;

a maximum thickness indicator having a visual or audible output and configured to indicate a visual or audible signal to a user of the shredder via the visual or audible output;

a controller configured to actuate the maximum thickness indicator and indicate the visual or audible signal to the user via the visual or audible output responsive to the detector detecting that the thickness of the at least one article is at least equal to a predetermined maximum thickness.]

[2. A shredder according to claim 1, wherein the maximum thickness indicator includes a light that is illuminated to indicate the signal to the user.]

[3. A shredder according to claim 1, wherein the maximum indicator includes an audible alarm that audibly indicates the signal to the user.]

[4. A shredder according to claim 1, wherein the controller is also configured to prevent the motor from driving the cutter elements in the shredding direction responsive to the detector detecting that the thickness of the at least one article is at least equal to the predetermined maximum thickness.]

[5. A shredder according to claim 1, wherein the maximum thickness indicator is included in a progressive indicator system coupled to the controller,

wherein the progressive indicator system is configured to indicate a detected thickness of the at least one article within a range of thicknesses up to and including the predetermined maximum thickness.]

[6. A shredder according to claim 5, wherein the progressive indicator system has a plurality of indicators, wherein each indicator is associated with a corresponding predetermined thickness of the at least one article within said range, the plurality of indicators including the maximum thickness indicator corresponding to the predetermined maximum thickness,

wherein the progressive indicator system activates the indicator associated with its respective corresponding predetermined thickness based on the detector detecting that the thickness of the at least one article is at least equal to the corresponding predetermined thickness.]

[7. A shredder according to claim 6, wherein the progressive indicator system comprises a plurality of lights.]

[8. A shredder according to claim 1, wherein the detector comprises a contact member that extends into the throat and is actuated in response to the article being inserted into the throat.]

[9. A shredder according to claim 8, wherein the detector further comprises a strain gauge configured to measure movement of the contact member and communicate the movement to the controller.]

[10. A shredder according to claim 8, wherein the detector further comprises a piezoelectric sensor configured to measure movement of the contact member and communicate the movement to the controller.]

[11. A shredder according to claim 8, wherein the detector further comprises an optical sensor configured to measure movement of the contact member and communicate the movement to the controller.]

[12. A shredder according to claim 11, wherein the optical sensor comprises an infrared LED and a dual die infrared receiver configured to detect the direction and amount of the movement.]

[13. A shredder according to claim 1, wherein the detector is also configured to detect a presence of the at least one article to be shredded being received by the throat, and wherein the controller is configured to operate the motor to drive the cutter elements in the shredding direction responsive to the detector detecting both the presence of the at least one article to be shredded being received by the throat and that the thickness thereof is less than the predetermined maximum thickness.]

[14. A shredder according to claim 1, wherein the detector is a thickness detector and the shredder further comprises a presence detector configured to detect a presence of the at least one article to be shredded being received by the throat,

wherein the controller is configured to operate the motor to drive the cutter elements in the shredding direction responsive to the presence detector detecting the presence of the at least one article to be shredded being received by the throat.]

[15. A shredder according to claim 14, wherein the controller is configured to operate the motor to drive the cutter elements in the shredding direction responsive to both the presence detector detecting the presence of the at least one article to be shredded being received by the throat and the thickness sensor detecting that the thickness thereof is less than the predetermined maximum thickness.]

16. A shredder comprising:

a housing having a throat open to an exterior of the housing for permitting a user to feed at least one article to be shredded;

a shredder mechanism received in the housing and including an electrically powered motor and cutter elements, the shredder mechanism enabling the at least one article fed into the throat to be shredded to be fed into the cutter elements and the motor being operable to drive the cutter elements in a shredding direction so that the cutter elements shred the articles fed therein;

a thickness detector configured to detect a thickness between opposing major surfaces of the at least one article to be shredded being received by the throat;

a maximum thickness indicator having a visual or audible output and configured to indicate a visual or audible signal to a user of the shredder via the visual or audible output;

a controller configured to actuate the maximum thickness indicator and indicate the visual or audible signal to the user via the visual or audible output responsive to the detector detecting that the thickness of the at least one article is at least equal to a predetermined maximum thickness;

wherein the detector is a thickness detector and the shredder further comprises a presence detector configured to detect a presence of the at least one article to be shredded being received by the throat, wherein the controller is configured to operate the motor to drive the cutter elements in the shredding direction responsive to the presence detector detecting the presence of the at least one article to be shredded being received by the throat;

wherein the controller starts the motor to drive the cutter elements in the shredding direction only in response to both the presence detector detecting the presence of the at least one article to be shredded being received by the throat and the thickness detector detecting that the thickness thereof is less than the predetermined maximum thickness.

17. A shredder according to claim 16, wherein the detector comprises a contact member that extends into the throat and is actuated in response to the article being inserted into the throat.

18. A shredder according to claim 17, wherein said thickness detector is a variable thickness detector for outputting a variable amount of movement of said contact member.

19. A shredder according to claim 18, wherein said thickness detector includes an optical sensor and indicators movable past the optical sensor by movement of said contact member to enable the variable amount of movement of said contact member to be output by the optical sensor.

20. A shredder according to claim 18, wherein the detector further comprises a strain gauge configured to measure movement of the contact member and communicate the movement to the controller.

21. A shredder according to claim 18, wherein the detector further comprises a piezoelectric sensor configured to measure movement of the contact member and communicate the movement to the controller.

22. A shredder according to claim 16, wherein said thickness detector includes a sensor and the contact member is coupled to a detectable element movable for detection by the sensor, and wherein said thickness detector is configured such that movement of said contact member in the throat amplifies movement of the detectable element at the sensor.

* * * * *